

MODEL
FGO 77

| | | | | | |
|------------------|---------------------|-------------------|------------|-----------------------|-------------------|
| RATED CAPACITY | CAPACITA' NOMINALE | m ³ /h | 77 | | |
| | | l/min | 1283 | | |
| | | CFM | 45 | | |
| Working pressure | Pressione Esercizio | bar | 7 | (Max pressure 16 bar) | |
| Weight | Peso | kg | 1 | | |
| Air connection | Attacchi Aria | IN / OUT | BSP-F 3/4" | | |
| Drain connection | Attacco Drenaggio | | 3/8" | | |
| Dimensions | Dimensioni | A | mm | 95 | |
| | | B | mm | 210 | |
| | | C | mm | 32 | (with Auto Drain) |
| | | D | mm | 89 | |
| | | E | mm | 180 | |

| Cartridge Cartucce | Type | Max dim. µm | Process | Max Temp °C | Pressure drop bar |
|-----------------------|------|----------------------------|--------------|----------------|----------------------|
| | P | 3 | interception | 100 | 0,08 |
| M | 1 | interception coalescing | 100 | 0,15 | |
| H | 0,01 | interception coalescing | 100 | 0,15 | |
| C | - | activated carbon | 60 | 0,08 | |

