


MODEL
DGO 106

RATED CAPACITY	m ³ /h	106	
	l/min	1767	
	SCFM	62	
Power supply	V/ph/Hz	230/1/50	
Power consumption	kW	0,320	
Full Load consumption	kW	0,35	
Rated absorpt.	A	1,45	
Full Load Current	A	1,66	
Lock. Rotor Current	A	6,00	
COP	w/w	2,28	
Weight	kg / lbs	26/57	
Air connection	IN / OUT	3/4"	BSP-F
Coolant type		R134a	
Volume of the gas	kg	0,50	
Inlet air temp.	°C / °F	35/95	max 70/158
Ambient temp.	°C / °F	25/77	max 50/122
Pressure dew point	°C / °F	3/37	
Working pressure	bar / psi	7/100	max 16/232

Standard features

Control panel	Electronic system type
Condenser cooling	Air cooled
Ventilator motor	Blower fan
Air/air heat exch.	Aluminium pack
Evaporator	Aluminium pack
Expansion method	Capillary tube
Separator type	Demister type
Compressor type	Reciprocating compressor type
Installation location	Indoor
Drain discharge	Time solenoid valve
Electric protection	IP 42

Performances & specification: +/- 5%


Dimensions

A	mm	345
B	mm	409
C	mm	480
D	mm	343
E	mm	100
F	mm	37
G	mm	67
H	mm	278