


MODEL
DGO 1800

RATED CAPACITY	m ³ /h	1800	
	l/min	30000	
	SCFM	1060	
Power supply	V/ph/Hz	400/3/50	
Power consumption	kW	3,050	
Full Load consumption	kW	3,11	
Rated absorpt.	A	6,73	
Full Load Current	A	6,89	
Lock. Rotor Current	A	50,00	
COP	w/w	3,44	
Weight	kg / lbs	250/551	
Air connection	IN / OUT	3"	BSP-F
Coolant type		R407C	
Volume of the gas	kg	4.75	
Inlet air temp.	°C / °F	35/95	max 70/158
Ambient temp.	°C / °F	25/77	max 50/122
Pressure dew point	°C / °F	3/37	
Working pressure	bar / psi	7/100	max 16/232

Standard features

Control panel	Electronic system type
Condenser cooling	Air cooled
Ventilator motor	Suction fan
Air/air heat exch.	Aluminium pack
Evaporator	Aluminium pack
Expansion method	Capillary tube
Separator type	Demister type
Compressor type	Scroll compressor type
Installation location	Indoor
Drain discharge	Time solenoid valve
Electric protection	IP 42

Performances & specification: +/- 5%

Dimensions

A	mm	657
B	mm	1156
C	mm	1650
D	mm	1041
E	mm	178
F	mm	334
G	mm	78
H	mm	1078