


**MODEL**
**DGO 9600**

<b>RATED CAPACITY</b>	m <sup>3</sup> /h	9600	
	l/min	160000	
	SCFM	5650	
<b>Power supply</b>	V/ph/Hz	400/3/50	
<b>Power consumption</b>	kW	14,350	
<b>Full Load consumption</b>	kW	14,55	
<b>Rated absorpt.</b>	A	25,24	
<b>Full Load Current</b>	A	25,43	
<b>Lock. Rotor Current</b>	A	225,00	
<b>COP</b>	w/w	3,58	
<b>Weight</b>	kg / lbs	700/1543	
<b>Air connection</b>	IN / OUT	DN200	
<b>Coolant type</b>		R407C	
<b>Volume of the gas</b>	kg	13.0	
<b>Inlet air temp.</b>	°C / °F	35/95	max 70/158
<b>Ambient temp.</b>	°C / °F	25/77	max 50/122
<b>Pressure dew point</b>	°C / °F	3/37	
<b>Working pressure</b>	bar / psi	7/100	max 14/203

**Standard features**

<b>Control panel</b>	Electronic system type
<b>Condenser cooling</b>	Air cooled
<b>Ventilator motor</b>	Suction fan
<b>Air/air heat exch.</b>	Aluminium pack
<b>Evaporator</b>	Aluminium pack
<b>Expansion method</b>	Capillary tube
<b>Separator type</b>	Demister type
<b>Compressor type</b>	Scroll compressor type
<b>Installation location</b>	Indoor
<b>Drain discharge</b>	Time solenoid valve
<b>Electric protection</b>	IP 42

Performances & specification: +/- 5%


**Dimensions**

<b>A</b>	mm	2113
<b>B</b>	mm	1406
<b>C</b>	mm	1765
<b>D</b>	mm	740
<b>E</b>	mm	400
<b>F</b>	mm	496
<b>G</b>	mm	158
<b>H</b>	mm	1248